



Topology optimization of a reversible crash protection using fluid – structure interaction

Andreasen, Casper Schousboe

Published in:
Eighth World Congress on Structural and Multidisciplinary Optimization

Publication date:
2009

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Andreasen, C. S. (2009). Topology optimization of a reversible crash protection using fluid – structure interaction. In *Eighth World Congress on Structural and Multidisciplinary Optimization: Book of Abstracts* <http://www.wcsmo8.org>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Topology optimization of a reversible crash protection using fluid – structure interaction

Casper Schousboe Andreassen, Ole Sigmund

Keywords: Class II problem, fluid-solid interaction, transient topology optimization, material interpolation, homogenization.

Topology optimization has proven a very successful method for obtaining optimized designs without a priori design considerations for a variety of mechanical problems [1]. This includes among others both solid and fluid mechanical problems. Topology optimization has earlier been applied for crashworthiness applications by the use of truss and frame models [2]. In this work a fluid saturated porous material with spatially varying microstructure is considered and the effect of internal dissipation is utilized.

The goal in this paper is to design auto mobile bumpers or crash barriers where reversible crash protection for impact is needed, meaning that the deceleration limitation does not origin from plasticity. Such an energy absorbing mechanism can be designed using a porous fluid saturated material which in its optimized configuration limits the deceleration during crash due to the dissipation and furthermore regains its original outer shape afterwards due to the elastic skeleton.

The methods used so far in the context of topology optimization of fluid mechanical problems uses the Brinkman formulation where the flow is penalized by introducing less penetrable material which in the limit acts as solid material [3]. This though neglects the stiffness problem and does not allow for designs where the structure and fluid interacts as this requires a well-defined boundary on which the stresses can be evaluated.

In order to include the interaction an alternative approach is used, namely to consider a class II problem, also known as soil-pore interaction in earth-mechanics, where the solid and fluid are inseparable and are represented in the same variables. The problem is transient and the consolidation equations were first introduced by Biot but this work elaborates on the formulation in [4,5].

An interpolation function is introduced for each of the constitutive parameters; stiffness, permeability and hydrostatic pressure dependency in order to use the topology optimization method. These interpolation functions origin from homogenization studies of a prescribed simple micro-structure which can be scaled according to macroscopic density.

By the specification of an objective function such as a prescribed deceleration curve [2] and the use of mathematical programming an optimized crash protector is designed.

[1] Bendsøe, M.P., Sigmund, O., (2004) *Topology Optimization - Theory, Methods and Applications*, 2nd ed., ISBN: 978-3540429920, Springer.

[2] C.B.W. Pedersen, (2004), *Crashworthiness design of transient frame structures using topology optimization*, Computer Methods in Applied Mechanical Engineering, 193: 653-678.

[3] Borrvall T., Petersson J., (2003), *Topology Optimization of fluids in Stokes flow*, International Journal of Numerical Methods in Fluids, 41: 77-107.

[4] Terada, K. , Ito, T. , Kikuchi, N., (1998) *Characterization of the mechanical behaviours of solid-fluid mixture by the homogenization method*, Computer Methods in Applied Mechanical Engineering, 153: 223-257

[5] Zienkiewicz, O.C., Taylor, R.L., (2000), *The Finite Element Method: Volume 1*, 5th edition, ISBN: 978-0750650496, Butterworth-Heinemann.